shop.pearlfiltration.com.au

service@pearlfiltration.com.au

INSTALLATION & OPERATION INSTRUCTIONS PUSH-FIT CONNECTIONS

Pearl Filtration Pty Ltd shall not be held liable for any damages whatsoever resulting from the use or installation of this product, regardless of the cause (including, but not limited to, material defects or workmanship). Installing, operating, or utilising this product in any way indicates the Buyer has read and accepted this statement and our Terms & Conditions of Trade, available to view on our website: pearlfiltration.com.au/shop/terms-conditions/

Warning:

This product is designed for indoor use, with town water of ambient temperature. Do <u>not</u> use this product with water that is microbiologically unsafe or declared not fit for drinking.

Refer to product datasheet for max. allowable operating pressure. All plumbing works should be carried out by a licenced plumber.

To Insert the Tube:

	- No. C. A. C.	
Step 1.	Remove any coloured clips from the fitting (if present)	
Step 2.	Cut the tube to the desired length. Ensure the cut is straight, clean and free from burs	
Step 3.	Push the tube into the fitting, ensuring it is pushed in as far as the fitting will allow	
Step 4.	Ensure the tube is properly secured in the fitting by gently pulling back on the tube	
Step 5.	Replace the coloured clips removed in Step 1 (optional) to their original positions	
Step 6.	Repeat Steps 1-5 for each fitting	
Step 7.	Test the system and monitor for leaks. If leaks are present, repeat Steps 1-5, taking particular care to check the tube is cut straight and pushed fully into the fitting	

To Remove the Tube:

